

NETTING



Crisp Websites Limited Pest Control Division

Maple Works
Old Shoreham Road
Hove
East Sussex
BN3 7ED
Tel: 0845 643 4601
Email: enquiries@crispwebsites.com
Web: www.gullstop.co.uk
www.pigeonstop.co.uk
www.birdstop.co.uk

AD – ADVANTAGES

Netting, when installed correctly provides total exclusion of all pest birds.

The netting Crisp Websites supplies is strong and versatile and will last in excess of 10 years in average UK sunlight conditions. Constructed from 12/6 UV stabilized twine, which is 0.30mm thick. It has a breaking strength of 14kg.

The twine is very thin and because it is available in black, stone and translucent, the net colour can be chosen to blend into the background, so that it is invisible.

DAD - DISADVANTAGES

For a successful Installation you will require a variety of fixtures and fittings, which may require an experience installer to fit.

UA – USES, APPLICATIONS

Netting can be used to prevent access to any bird in or on any architectural structure. The net can be installed horizontally, vertically or in any direction required to achieve the desired effect.

AI – Assembly, Instructions

The netting is available in stock sizes of 5m x 5m, 5m x 10m, 10m x 10m, 10m x 15m and 20m x 20m. we can however cut any net to any size you require.

There are kits available to make ordering easy, with everything required for installing the net. Fixings will depend on which substrate you are fixing the netting to, masonry, sheet metal and steel work all require different fixings.

For detailed installation guidelines please refer to our instruction manual, which can be downloaded on www.gullstop.co.uk

MF – MATERIALS, FINISHES

Crisp Websites supplies two ranges of fixings, budget which is made from galvanized steel, and professional which is made from stainless steel.

TS – TECHNICAL SUPPORT

Crisp Websites' staff are all fully trained and are available Mon-Friday 9am – 6pm to provide full telephone support.

SPECIFICATION GUIDELINES

GENERAL

1.1 DESCRIPTION

- 1.1.1 Install Crisp Websites' Netting to block access to pest birds from any open area or opening to prevent birds from nesting or perching, where damage may be caused from dropping, nesting materials, or they are simply becoming a nuisance.

1.2 QUALITY ASSURANCE

- 1.2.1 Obtain technical literature from supplier, telephone consultation and plan/photograph evaluation.
- 1.2.2 Utilize certified installers, in your area who carry the proper insurance coverage. For recommendations of approved installers contact Crisp Websites.

1.3 SUBMITTALS

- 1.3.1 Submit manufacturer's samples and other descriptive material.

1.4 PRODUCT HANDLING

- 1.4.1 Protect Netting and fixtures and fittings from damage before, during and after installation.
- 1.4.2 If damage occurs to the netting system, make all replacements immediately.

PRODUCTS

2.1 MODEL DESIGNATION

- 2.2.1 Seagull Netting, 75mm mesh
- 2.2.2 Pigeon Netting, 50mm mesh
- 2.2.3 Pheasant Netting, 40mm mesh
- 2.2.4 Starling Netting, 28mm mesh
- 2.2.5 Sparrow Netting, 19mm mesh.

All netting is available in either black, stone or translucent.

- 2.2.6 "No-Flame" flame retardant netting is also available in the following mesh sizes: 75mm, 50mm, 28mm and 19mm.

NETTING

MATERIAL

Material: HDPE Ultra Violet stabilized twine.

Construction: 630 denier (0.30mm thick) monofilament HDPE which is then twisted x 2, then x 3 to make the finished twine approximately 1mm in diameter, with a 12/6 construction.

Breaking Strength: 14kg to ISO1805

2.3 MOUNTING SYSTEMS

2.3.1 **Solid Steel:** for corner attachments use Beam clamps. For intermediates use hammer on beam clamps.

2.3.2 **Sheet Metal:** for corner attachments use cladding bolts or beam bolts. For intermediates use angle brackets with self drill screws and rubber bonded washers, or net guides.

2.3.3 **Masonry:** for corner fixings use corner eye bolts. For intermediate fixings use screw eyes with wall plugs.

2.3.4 **Timber:** for corner fixings use vine eyes. For intermediate fixings use screw eyes or screw pins.

2.3.5 **Wire Rope:** 7 x 7 construction, 2mm diameter wire rope. Use copper ferrules and a crimp tool, or cable grips and a wire rope grip nut spinner for finishing off the cable. Use a barrel strainer at every 10m or around no more than one corner to tension the wire rope.

2.3.6 **Cable to Net fixings:** Use hog rings and a hog ring stapler, with netting corner ties where appropriate.

2.3.7 Correct intermediate placements is as follows: 1m intervals for 75mm and 50mm mesh. 0.5m intervals for 40mm and 28mm mesh. 0.3m intervals for 19mm mesh.

EXECUTION

3.1 EXAMINATION

3.1.1 Examine installation area. Notify architect of detrimental work conditions.

3.1.2 Do not proceed until conditions are corrected.

3.2 SURFACE PREPARATION

3.2.1 Bird droppings shall be removed in a safe manner; large quantities shall be removed and disposed of by licensed waste removal carrier. Work areas shall be cleaned and repair work shall be done in areas which will be excluded by netting.

3.2.2 Remove or repair articles that may damage the Post & Wire system after installation, such as tree limbs and loose parts of the building.

3.3 INSTALLATION

3.3.1 Install Netting as recommended in the installation instructions, which can be downloaded from www.gullstop.co.uk Ensure there are no gaps to prevent birds from entering into the area behind the netting.

3.3.2 The correct mesh size shall be specified to ensure exclusion of the correct pest bird.

3.3.3 Ensure the netting is installed and tensioned as tightly as possible to make the installation effect, long lasting and prevent causing any harm to the birds.

3.3.3 At every post there should be a spring and termination of the wire section using crimps. The next section simply continues from the same post.

3.4 INSPECTION

3.4.1 Visually inspect the netting for poor adherence to mounting surfaces, or other problems related to poor installation or surface preparation.

3.4.2 Repair as necessary, immediately.

OM – OPERATION, MAINTENANCE

If the netting is installed by professionally trained installers, or per our recommendations, the product should be virtually maintenance free. Wind or rain will not damage the net as long as it is secured per our specifications.

